

Ordering code DMD 331

DMD 331

□□□ - □ - □□□□ - □ - □ - □□□ - □□□ - □ - □□□

Pressure										
differential pressure	7	3	0							
Nominal pressure range [bar]										
0.2				F						
0.4				A						
1.0				B						
2.5				C						
6.0				D						
16				E						
customer				9						consult
Differential pressure rang [bar]										
	F	A	B	C	D	E				
0.02	■						0	2	0	0
0.04	■	■					0	4	0	0
0.10	■	■	■				1	0	0	0
0.25	■	■	■	■			2	5	0	0
0.40	■	■	■	■	■		4	0	0	0
0.60	■	■	■	■	■	■	6	0	0	0
1.0	■	■	■	■	■	■	1	0	0	1
2.5	■	■	■	■	■	■	2	5	0	1
4.0	■	■	■	■	■	■	4	0	0	1
6.0	■	■	■	■	■	■	6	0	0	1
10	■	■	■	■	■	■	1	0	0	2
16	■	■	■	■	■	■	1	6	0	2
customer							9	9	9	9
Output										
4 ... 20 mA / 2-wire										1
0 ... 10 V / 3-wire										3
customer										9
Accuracy										
0.5 %										5
customer										9
Electrical connection										
Male and female plug ISO 4400										1
Brad Harrison®- Mini Change										B
customer										9
Mechanical connection										
G1/2" EN 837										2
7/16" UNF DIN 3866										U
G1/4" internal thread										J
customer										9
Seals										
FKM										1
customer										9
Special version										
standard										0
customer										9

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

