Fax: +49 (0) 92 35 / 98 11 -11

BD | SENSORS® pressure measurement

Ordering code LMK 358H

LMK 358H

□□□-□□□□-□-□-□-□-□-□-□□□-□□□-□□□

Pressure			
in bar		445	
in mH_2O		446	
Input	**[mH_2O]**	**[bar]**	
0.60	0.06	0600	
1.60	0.16	1600	
4.00	0.40	4000	
10	1.0	1001	
20	2.0	2001	
50	5.0	5001	
100	10	1002	
customer		9999	consult
Housing			
Stainless steel 1.4404 (316L)		1	
customer		9	consult
Diaphragm			
Ceramics Al_2O_3 96%		2	
Ceramics Al_2O_3 99.9%		C	
customer		9	consult
Output			
HART®-communication 4 ... 20 mA / 2-wire		H	
HART®-communication Intrinsic safety 4 ... 20 mA / 2-wire		I	
customer		9	consult
Seals			
FKM		1	
EPDM		3	
customer		9	consult
Electrical connection			
PVC-cable [1]		1	
PUR-cable [1]		2	
FEP-cable [1]		3	
TPE-cable		4	
customer		9	consult
Accuracy			
standard	0.2 %	B	
option	0.1 % [2]	1	
customer		9	consult
Cable length			
in m		999	
Special version			
standard		000	
prepared for mounting with stainless steel pipe [3]		106	
cable protection with stainless steel corrugated pipe with pipe length in m		103	999 consult
customer		999	consult

[1] cable with integrated air tube for atmospheric pressure reference
[2] only possible for $P_N \geq 0{,}60$ bar
[3] stainless steel pipe is not part of the supply

HART® is a registered trade mark of HART Communication Foundation

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

BD SENSORS GmbH
BD-Sensors-Straße 1
D - 95199 Thierstein
Telefon +49 (0) 92 35 / 98 11- 0
Telefax +49 (0) 92 35 / 98 11- 11
www.bdsensors.com
info@bdsensors.de