Fax: +49 (0) 92 35 / 98 11 -11

BD SENSORS® pressure measurement

Ordering code LMK 382H

LMK 382H □□□-□□□□-□-□-□-□-□-□-□□□-□□□

Pressure				
in bar		5 6 5		
in mH_2O		5 6 6		
Input	[mH_2O]	[bar]		
	0.60	0.06	0 6 0 0	
	1.60	0.16	1 6 0 0	
	4.00	0.40	4 0 0 0	
	10	1.0	1 0 0 1	
	20	2.0	2 0 0 1	
	50	5.0	5 0 0 1	
	100	10	1 0 0 2	
		customer	9 9 9 9	consult
Housing				
Stainless steel 1.4404 (316L)			1	
customer			9	consult
Diaphragm				
Ceramics Al_2O_3 96%			2	
Ceramics Al_2O_3 99.9%			C	
customer			9	consult
Output				
HART®-communication 4 ... 20 mA / 2-wire			H	
HART®-communication Intrinsic safety 4 ... 20 mA / 2-wire			I	
customer			9	consult
Seals				
FKM			1	
EPDM			3	
FFKM			7	
customer			9	consult
Electrical connection				
PVC-cable [1]			1	
PUR-cable [1]			2	
FEP-cable [1]			3	
TPE-cable [1]			4	
customer			9	consult
Accuracy				
standard	0.2 %		B	
option	0.1 % [2]		1	
customer			9	consult
Cable length				
in m			9 9 9	
Special version				
standard			0 0 0	
prepared for mounting with stainless steel pipe [3]			5 0 2	
flange version			5 1 0	
customer			9 9 9	consult

[1] cable with integrated air tube for atmospheric pressure reference
[2] only possible for $P_N \geq 0{,}60$ bar
[3] stainless steel pipe is not part of the supply

HART® is a registered trade mark of HART Communication Foundation

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

BD SENSORS GmbH
BD-Sensors-Straße 1
D - 95199 Thierstein
Telefon +49 (0) 92 35 / 98 11- 0
Telefax +49 (0) 92 35 / 98 11- 11
www.bdsensors.com
info@bdsensors.de