Fax: +49 (0) 92 35 / 98 11 -11

BD SENSORS® pressure measurement

Ordering code LMP 308i

LMP 308i

□□□-□□□□-□-□-□-□-□-□-□□□-□□□-□□□

Pressure			
in bar	440		
in mH_2O	441		
Input	[mH_2O]	[bar]	
	4.0	0.40	4000
	10	1.0	1001
	20	2.0	2001
	40	4.0	4001
	100	10	1002
	200	20	2002
customer			9999 consult
Housing			
Stainless steel 1.4404 (316L)			1
customer			9 consult
Diaphragm			
Stainless steel 1.4435 (316L)			1
customer			9 consult
Output			
4 ... 20 mA / 2-wire			1
Intrinsic safety 4 ... 20 mA / 2-wire			E
0 ... 10 V / 3-wire			3
customer			9 consult
Seals			
FKM			1
EPDM			3
customer			9 consult
Electrical connection			
PVC-cable [1]			1
PUR-cable [1]			2
FEP-cable [1]			3
customer			9 consult
Accuracy			
0.1 % [2]			1
customer			9 consult
Cable length			
in m			999 consult
Version			
standard (with communicaton interface) [3]			121
prepared for mounting with stainless steel pipe [4]			126 consult
cable protection with stainless steel corrugated pipe with pipe length in m			123 999 consult
customer			999 consult

[1] cable with integrated air tube for atmospheric pressure reference

[2] available on request: calibration of individual pressure range higher than 400 mbar with accuracy 0.1 %

[3] Software, interface and cable have to be order separately (Ordering code: CIS-Set 510; Software appropriate for Windows® 95, 98, 2000, NT Version 4.0 or newer and XP)

[4] stainless steel pipe is not part of the supply

Windows® is a registrated trademark of Microsoft Corporation

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

BD SENSORS GmbH
BD-Sensors-Straße 1
D - 95199 Thierstein
Telefon +49 (0) 92 35 / 98 11- 0
Telefax +49 (0) 92 35 / 98 11- 11
www.bdsensors.com
info@bdsensors.de