

DCT 531P



Industrial Pressure Transmitter with RS485 Modbus RTU

Process Connections with Flush Welded
Stainless Steel Diaphragm

accuracy according to IEC 60770:
standard: $\leq \pm 0.25$ % FSO
option: $\leq \pm 0.1$ % FSO

Nominal pressure

from 0 ... 100 mbar up to 0 ... 40 bar

Output signal

RS485 with Modbus RTU protocol

Special characteristics

- ▶ hygienic version
- ▶ diaphragm with low surface roughness
- ▶ CIP / SIP-cleaning up to 150 °C
- ▶ ingress protection IP 67 / IP 69
- ▶ reset function

Optional versions

- ▶ different process connections
- ▶ cooling element for media temperatures up to 200 °C

The pressure transmitter DCT 531P was designed for use in the food / beverage and pharmaceutical industry. The compact design with hygienic versions guarantees an outstanding performance in terms of accuracy, thermal behaviour and long term stability.

The integrated RS485 interface is characterized by a robust and reliable data transmission that works failure-free even over long distances.

Additionally, the modular construction concept of the device allows to combine different electrical and mechanical connections, so it is easy to adapt the pressure transmitter to different conditions on-site.

Preferred areas of use are



Food and beverage



Pharmaceutical industry

Material and test certificates

- ▶ Inspection certificate 3.1 according to EN 10204
- ▶ Test report 2.2 according to EN 10204



Modbus®

DCT 531P

Industrial Pressure Transmitter with RS485 Modbus RTU

Technical Data

Input pressure range ¹									
Nominal pressure gauge	[bar]	-1...0	0.10	0.16	0.25	0.40	0.60	1	1.6
Nominal pressure absolute	[bar]	-	-	-	-	0.40	0.60	1	1.6
Overpressure	[bar]	5	0.5	1	1	2	5	5	10
Burst pressure ≥	[bar]	7.5	1.5	1.5	1.5	3	7.5	7.5	15
Nominal pressure gauge / absolute	[bar]	2.5	4	6	10	16	25	40	
Overpressure	[bar]	10	20	40	40	80	80	105	
Burst pressure ≥	[bar]	15	25	50	50	120	120	210	
Vacuum resistance		p _N > 1 bar: unlimited vacuum resistance p _N ≤ 1 bar: on request							
¹ consider the pressure resistance of fitting and clamps									

Output signal / Supply	
Standard	RS485 with Modbus RTU protocol / V _s = 9 ... 32 V _{DC}
Performance	
Accuracy ²	standard ≤ ± 0.25 % FSO option ≤ ± 0.10 % FSO
Long term stability	≤ ± 0.1 % FSO / year at reference conditions
Measuring rate	500 Hz
Delay time	500 msec
² accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)	

Thermal effects (offset and span) ³				
Nominal pressure p _N	[bar]	-1 ... 0	< 0.40	≥ 0.40
Tolerance band	[% FSO]	≤ ± 0.75	≤ ± 1.5	≤ ± 0.75
In compensated range ⁴	[°C]	-20 ... 85	0 ... 50	-20 ... 85
³ an optional cooling element can influence thermal effects for offset and span depending on installation position and filling conditions				
⁴ the minimum compensation temperature depends on the filling fluid used				

Permissible temperatures		
Filling fluid	silicone oil	food compatible oil
Medium ⁵	-40 ... 125 °C	-10 ... 125 °C
Medium with cooling element 200 °C	overpressure: -40 ... 200 °C vacuum: -40 ... 150 °C ⁶	overpressure: -10 ... 200 °C vacuum: -10 ... 150 °C ⁶
Electronics / environment	-40 ... 85 °C	
Storage	-40 ... 100 °C	
⁵ max. temperature of the medium for nominal pressure gauge > 0 bar: 150 °C for 60 minutes with a max. environmental temperature of 50 °C		
⁶ also for p _{abs} ≤ 1 bar		

Electrical protection	
Short-circuit protection	permanent
Reverse polarity protection	on supply connection no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326

Mechanical stability	
Vibration	according to DIN EN 60068-2-6 G 1/2": 20 g RMS (25...2000 Hz) others: 10 g RMS (25...2000 Hz)
Shock	according to DIN EN 60068-2-27 G 1/2": 500 g / 1 msec others: 100 g / 1 msec

Filling fluids	
Standard	silicone oil
Option	food compatible oil according to 21CFR178.3570 (Mobil SHC Cibus 32; Category Code: H1; NSF Registration No.: 141500) others on request

DCT 531P

Industrial Pressure Transmitter with RS485 Modbus RTU

Technical Data

Materials		
Housing / electrical connection	stainless steel 1.4404 (316 L)	
Pressure port	stainless steel 1.4435 (316 L)	
Diaphragm	stainless steel 1.4435 (316 L)	
Seal	standard: FKM medium temperatures $\leq 200\text{ }^{\circ}\text{C}$ option: FFKM (recommended for medium temperatures $> 200\text{ }^{\circ}\text{C}$) without: Clamp, dairy pipe, Varivent® others on request	
Media wetted parts	pressure port, seal, diaphragm	
Miscellaneous		
Weight	approx. 200 g	
Current consumption	max. 10 mA	
Surface roughness	pressure port $R_a < 0.8\text{ }\mu\text{m}$ (media wetted parts) diaphragm $R_a < 0.15\text{ }\mu\text{m}$ weld seam $R_a < 0.8\text{ }\mu\text{m}$	
Operational life	100 million load cycles	
Installation position	any (standard calibration in a vertical position with the pressure port connection down; differing installation position for $p_N \leq 2\text{ bar}$ have to be specified in the order)	
CE-conformity	EMC Directive: 2014/30/EU	
Wiring diagram		
RS 485 / Modbus RTU		
Pin configuration / electrical connection		
Electrical connection	M12x1 / metal (5-pin), IP 67	
Supply +	1	
Supply -	3	
A (+)	2	
B (-)	4	
Reset	5	
Shield	plug housing	

DCT 531P

Industrial Pressure Transmitter with RS485 Modbus RTU

Technical Data

Dimensions / mechanical connection (mm / in)

⇒ metric threads and other versions on request

Configuration Modbus RTU					
Standard configuration	001	-	1	-	1
Address					
Address	001				
	...				
	247				
Baud Rate					
4800 Bd			0		
9600 Bd			1		
19200 Bd			2		
38400 Bd			3		
Parity					
None					0
Odd					1
Even					2
Configuration code (to specify with order)		-		-	

© 2021 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code DCT 531P

DCT 531P



Pressure											
	absolute	5	0	1							
	gauge	5	0	2							
Input											
	[bar]										
	0.10	1			1	0	0	0			
	0.16	1			1	6	0	0			
	0.25	1			2	5	0	0			
	0.40				4	0	0	0			
	0.60				6	0	0	0			
	1.0				1	0	0	1			
	1.6				1	6	0	1			
	2.5				2	5	0	1			
	4.0				4	0	0	1			
	6.0				6	0	0	1			
	10				1	0	0	2			
	16				1	6	0	2			
	25				2	5	0	2			
	40				4	0	0	2			
	-1 ... 0				X	1	0	2			
	customer				9	9	9	9			consult
Output											
	RS485 Modbus RTU				L	5					
Accuracy											
Standard:	0.25 % FSO				2						
Option:	0.10 % FSO				1						
	customer				9						consult
Electrical connection											
	male plug M12x1 (5-pin) / metal					N	1	1			
	customer					9	9	9			consult
Mechanical connection											
	G1/2" DIN 3852 flush (p _N ≥ 1 bar)					Z	0	0			
	G1" DIN 3852 flush					Z	S	1			
	G 1" cone					K	S	1			
	Clamp DN 25 DIN 32676 (p _N ≤ 16 bar)					C	6	1			
	Clamp DN 32 DIN 32676 (p _N ≤ 16 bar)					C	6	2			
	Varivent® DN 40/50					P	4	1			
	customer					9	9	9			consult
Diaphragm											
	stainless steel 1.4435 (316L)						1				
	customer						9				consult
Seal											
for clamp, dairy pipe, Varivent®:	without						0				
for inch thread - standard:	FKM						1				
for inch thread - option:	FFKM						7				
	customer						9				consult
Filling fluid											
	silicone oil						1				
	food compatible oil (FDA)						2				
	customer						9				consult
Special version											
	standard						0	0	0		
	with cooling element up to 200°C						2	0	0		
	customer						9	9	9		consult

¹ absolute pressure possible from 0.4 bar

Varivent® is a brand name of GEA Tuchenhagen GmbH, Hastelloy® is a brand name of Haynes International Inc.

© 2020 BD|SENSORS GmbH - The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.