

DCT 531

Industrial Pressure Transmitter with RS485 Modbus RTU

Stainless Steel Sensor

accuracy according to IEC 61298-2:
0.25 % FSO



Nominal pressure

from 0 ... 100 mbar up to 0 ... 400 bar

output signal

RS485 with Modbus RTU protocol

Special characteristic

- ▶ pressure value
- ▶ perfect thermal behaviour
- ▶ excellent long term stability
- ▶ reset function

Optional versions

- ▶ pressure port
G 1/2" flush up to max. 40 bar
- ▶ pressure sensor welded
- ▶ customer specific versions

The DCT 531 with RS485 interface uses the communication protocol Modbus RTU which has found the way in industrial communication as an open protocol. The Modbus protocol is based on a master slave architecture with which up to 247 slaves can be questioned by a master.

Due to the usage of high quality materials and components, the DCT 531 is suitable for almost every industrial application, if the medium is compatible with stainless steel 316L.

The modular concept of the device allows customized mechanical connections, so it is easy to adapt the pressure transmitter to different conditions on-site.

Preferred areas of use are



Plant and machine engineering



Energy industry



Modbus®

Input pressure range												
Nominal pressure gauge	[bar]	-1...0	0.10	0.16	0.25	0.40	0.60	1	1.6	2.5	4	6
Nominal pressure absolute	[bar]	-	-	-	-	0.40	0.60	1	1.6	2.5	4	6
Overpressure	[bar]	5	0.5	1	1	2	5	5	10	10	20	40
Burst pressure \geq	[bar]	7.5	1.5	1.5	1.5	3	7.5	7.5	15	15	25	50

Nominal pressure gauge / absolute	[bar]	10	16	25	40	60	100	160	250	400	
Overpressure	[bar]	40	80	80	105	210	600	600	1000	1000	
Burst pressure \geq	[bar]	50	120	120	210	420	1000	1000	1250	1250	
Vacuum resistance		$p_N \geq 1$ bar: unlimited vacuum resistance					$p_N < 1$ bar: on request				

Output signal	
Digital	RS 485 with Modbus RTU protocol (pressure)

Supply	
Direct current	$V_S = 9 \dots 32 V_{DC}$

Performance	
Accuracy ¹	$\leq \pm 0.25$ % FSO
Long term stability	$\leq \pm 0.1$ % FSO / year at reference conditions
Measuring rate	500 Hz
Delay time	500 msec

¹ accuracy according to IEC 61298-2 – limit point adjustment (non-linearity, hysteresis, repeatability)

Thermal effects (offset and span)	
Tolerance band	$\leq \pm 0.75$ % FSO
in compensated range	-20 ... 85 °C

Permissible temperatures	
Medium	-40 ... 125 °C
Electronics / environment	-40 ... 85 °C
Storage	-40 ... 100 °C

Electrical protection	
Short-circuit protection	permanent
Reverse polarity protection	on supply connection no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326

Mechanical stability	
Vibration	20 g RMS / 10 ... 2000 Hz according to DIN EN 60068-2-6
Shock	500 g / 1 msec half sine according to DIN EN 60068-2-27

Materials	
Pressure port / housing	stainless steel 1.4404 (316 L)
Seals	standard: FKM option: EPDM; welded version ² (for $p_N \leq 40$ bar) others on request
Diaphragm	stainless steel 1.4435 (316 L)
Media wetted parts	pressure port, seal, diaphragm


² welded version only with pressure ports according to EN 837 and NPT, $p_N \leq 40$ bar

Miscellaneous	
Weight	approx. 210 g
Ingress protection	IP 67
Current consumption	max. 10 mA
Operational life	100 million load cycles
Installation position	any ³
CE-conformity	EMC Directive: 2014/30/EU Pressure Equipment Directive: 2014/68/EU (module A) ⁴

³ Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviations in the zero point for pressure ranges $p_N \leq 1$ bar.

⁴ This directive is only valid for devices with maximum permissible overpressure > 200 bar


Wiring diagram	
----------------	--



Pin configuration / electrical connection		
Electrical connection	M12x1, metal (5-pin)	
Supply +	1	
Supply -	3	
A (+)	2	
B (-)	4	
Reset	5	
Shield	plug housing	


Dimensions (mm / in)

standard



⇒ metric threads and other versions on request

options



Configuration Modbus RTU						
Standard configuration	001	-		1	-	1
Address						
Address	001					
	...					
	247					
Baud Rate						
4800 Bd				0		
9600 Bd				1		
19200 Bd				2		
38400 Bd				3		
Parity						
None						0
Odd						1
Even						2
Configuration code (to specify with order)						
		-			-	

© 2025 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code DCT 531

DCT 531



Pressure		D	C	7																						
	gauge	D	C	7																						
	absolute ¹	D	C	8																						
Input																										
	[bar]																									
	0.10	1			1	0	0	0																		
	0.16	1			1	6	0	0																		
	0.25	1			2	5	0	0																		
	0.40				4	0	0	0																		
	0.60				6	0	0	0																		
	1.0				1	0	0	1																		
	1.6				1	6	0	1																		
	2.5				2	5	0	1																		
	4.0				4	0	0	1																		
	6.0				6	0	0	1																		
	10				1	0	0	2																		
	16				1	6	0	2																		
	25				2	5	0	2																		
	40				4	0	0	2																		
	60				6	0	0	2																		
	100				1	0	0	3																		
	160				1	6	0	3																		
	250				2	5	0	3																		
	400				4	0	0	3																		
	-1 ... 0				X	1	0	2																		
	customer				9	9	9	9													consult					
Output																										
	RS485 Modbus RTU								L	5																
Accuracy																										
	0.25 % FSO																				2					
	customer																				9	consult				
Electrical connection																										
	male plug M12x1 (5-pin) / metal																				N	1	1			
	customer																				9	9	9	consult		
Mechanical connection																										
	G1/2" DIN 3852																					1	0	0		
	G1/2" EN 837																					2	0	0		
	G1/4" DIN 3852																					3	0	0		
	G1/4" EN 837																					4	0	0		
	G1/2" DIN 3852 with semi-flush sensor ²																					F	0	0		
	G1/2" DIN 3852 open pressure port ²																					H	0	0		
	1/2" NPT																					N	0	0		
	1/4" NPT																					N	4	0		
	customer																					9	9	9	consult	
Seal																										
	FKM																						1			
	EPDM																						3			
	without (welded version) ³																						2	consult		
	customer																						9	consult		
Special version																										
	standard																						0	0	0	
	customer																						9	9	9	consult

¹ absolute pressure possible from 0.4 bar

² not possible for nominal pressure $p_N > 40$ bar

³ welded version only with pressure ports according to EN 837 and NPT, possible for $p_N \leq 40$ bar

© 2023 BD|SENSORS GmbH - The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.