



## **Product characteristics**

- cost-efficient ABS case
- for connecting 2-wire submersible transmitters
- integrated pressure balance item
- 2 signal lines

## **Optional versions**

- Version for two independent 2 wire circuits
- overvoltage protection
- ▶ HART<sup>®</sup> connection

The terminal box KL 2 is intended for the professional electrical connection of submersible level transmitters. Thus, it is a cost-effective alternative to our well proven aluminium terminal box KL 1.

A pressure balance item is responsible for the compensation of atmospheric pressure variations. On the supply side a cable without ventilation tube can be used.

Vertical terminal clamps enable easy connection of cables inside the case.

The KL 2 with optional overvoltage protection is additionally equipped with surge arresters with a nominal discharge current of 10 kA.

As a further option the KL 2 is available with a  $HART^{\odot}$  connection.





www.bdsensors.com info@bdsensors.de





	Ordering code KL 2	
KL 2 - ZB.601		
Version		
standard	2 0 0	
over voltage protection	2 0 1	
version with 2 channels <sup>1</sup>	2 2 0	
version with 2 channels and over voltage protection <sup>1</sup>	2 2 1	
HART <sup>®</sup> communication interface	2 H 0	
HART <sup>®</sup> communication interface and over voltage protection	2 H 1	
Special version		
standard	0 0 0 9 9 9	
customer	9 9 9	consult

<sup>1</sup> Version for 2 independent 2 wire circuits

HART<sup>®</sup> is a registered trade mark of HART Communication Foundation