

LMP 308i

Separable Stainless Steel Probe Precision

Stainless Steel Sensor

accuracy according to IEC 60770: 0.1 % FSO



Nominal pressure

from 0 ... 4 mH₂O up to 0 ... 200 mH₂O

Output signals

2-wire: 4 ... 20 mA
3-wire: 0 ... 10 V
others on request

Special characteristics

- ▶ diameter 35 mm
- ▶ cable and sensor section separable
- ▶ excellent accuracy
- ▶ communication connection
- ▶ thermal error in compensated range
-20 ... 70 °C: 0.2 % FSO
TC 0.02 % FSO / 10K
- ▶ Turn-Down 1:10

Optional versions

- ▶ IS-version zone 0
- ▶ cable protection via corrugated pipe
- ▶ mounting accessories as cable gland and terminal clamp in stainless steel
- ▶ different kinds of cables
- ▶ different kinds of seal materials

The separable precision stainless steel probe LMP 308i is designed for continuous fill level and level measurement of water and liquid mediums. The signal processing of sensor signal is done by digital electronics with 16-bit analog digital converter. Consequently it is possible to conduct an active compensation of sensor intrinsic deviations from normal conditions like nonlinearity and thermal error.

In order to facilitate stock-keeping and maintenance the transmitter body is plugged to the cable assembly with a connector and can be changed easily.

Preferred areas of use are

Water / filtrated Sewage

ground water level measurement



level measurement in wells and open waters / rain spillway basin

level measurement in container

water treatment plants

water recycling




Input pressure range ¹							
Nominal pressure gauge	[bar]	0.40	1	2	4	10	20
Level	[mH ₂ O]	4	10	20	40	100	200
Overpressure	[bar]	2	5	10	20	40	80
Burst pressure	[bar]	3	7.5	15	25	50	120
¹ On customer request we adjust the device within the turn-down-possibility by software on the required pressure range.							
Output signal / Supply							
Standard	2-wire: 4 ... 20 mA / V _S = 12 ... 36 V _{DC} with RS-232 communication interface						
Option IS-protection	2-wire: 4 ... 20 mA / V _S = 14 ... 28 V _{DC}						
Options	3-wire: 0 ... 10 V / V _S = 14 ... 36 V _{DC}						
Performance							
Accuracy	IEC 60770 ² : ≤ ± 0.1 % FSO						
Performance after turn-down (TD)	no change of accuracy ³ formula for accuracy calculating (for nominal pressure gauge ≤ 0.40 bar see note 3): ≤ ± [0.1 + 0.015 x turn-down] % FSO with turn-down = nominal pressure range / adjusted range e.g. following accuracy can be calculated for turn-down 1:10: ≤ ± (0.1 + 0.015 x 10) % FSO viz. the accuracy is ≤ ± 0.25 % FSO						
- TD ≤ 1:5							
- TD > 1:5							
Permissible load	current 2-wire: R _{max} = [(V _S - V _{S min}) / 0.02 A] Ω voltage 3-wire: R _{min} = 10 kΩ						
Influence effects	supply: 0.05 % FSO / 10 V load: 0.05 % FSO / kΩ						
Long term stability	≤ ± (0.1 x turn-down) % FSO / year at reference conditions						
Response time	ca. 200 msec						
Adjustability	following parameters can be adjusted (interface / software needed ⁴) electronic damping: 0 ... 100 sec offset: 0 ... 90 % FSO turn-down of span: max. 1:10						
² accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)							
³ nominal pressure gauges ≤ 0,40 bar are excluded; for these the calculation of accuracy is as follows: ≤ ± (0.1 + 0.02 x turn-down) % FSO e.g. torn-down 1:3: ≤ ± (0.1 + 0.02 x 3) % FSO viz. the accuracy is ≤ ± 0.16 % FSO							
⁴ software, interface and cable must separate be ordered (software is compatible with Windows [®] 95, 98, 2000, NT from version 4.0 or higher and XP)							
Thermal effects (Offset and Span)							
Tolerance band	[% FSO]	≤ ± (0.2 x turn-down) in compensated range -20 ... 70 °C					
TC	[% FSO / 10 K]	± (0.2 x turn-down) in compensated range -20 ... 70 °C					
Permissible temperatures		medium: -20 ... 70 °C storage: -25 ... 70 °C electronics / enviroment: -25 ... 65 °C					
Electrical protection ⁵							
Short-circuit protection	permanent						
Reverse polarity protection	no damage, but also no function						
Electromagnetic compatibility	emission and immunity according to EN 61326						
⁵ additional external overvoltage protection unit in terminal box KL 1 or KL 2 with atmospheric pressure reference available on request							
Electrical connection							
Cable with sheath material ⁶	PVC (-5 ... 70 °C) grey PUR (-20 ... 70 °C) black FEP ⁷ (-20 ... 70 °C) black others on request						
⁶ cable with integrated air tube for atmospheric pressure reference							
⁷ do not use freely suspended probes with an FEP cable if effects due to highly charging processes are expected							
Materials (media wetted)							
Housing	stainless steel 1.4404 (316L)						
Seals	FKM, EPDM, others on request						
Diaphragm	stainless steel 1.4435 (316L)						
Protection cap	POM						
Explosion protection (only for 4 ... 20 mA / 2-wire)							
Approvals DX19-LMP 308 i	IBExU 10 ATEX 1068 X / IECEx IBE 12.0027X zone 0: II 1G Ex ia IIC T4 Ga zone 20: II 1D Ex ia IIIC T 85°C Da						
Safety technical maximum values	U _i = 28 V, I _i = 93 mA, P _i = 660 mW, C _i ≈ 0 nF, L _i ≈ 0 μH, the supply connections have an inner capacity of max. 27 nF to the housing						
Ambient temperature range	in zone 0: -20 ... 60 °C with p _{atm} 0.8 bar up to 1.1 bar in zone 1 or higher: -20 ... 65 °C						
Connecting cables (by factory)	cable capacitance: signal line/shield also signal line/signal line: 160 pF/m cable inductance: signal line/shield also signal line/signal line: 1 μH/m						
Miscellaneous							
Current consumption	signal output current: max. 25 mA						
Weight	approx. 250 g (without cable)						
Ingress protection	IP 68						
CE-conformity	EMC Directive: 2014/30/EU						
ATEX Directive	2014/34/EU						

LMP 308i

Precision Stainless Steel Probe

Accessories

Wiring diagram / connector





Pin configuration

Electrical connection	Binder series 723 ⁸ (5-pin) / 2-wire	Binder series 723 ⁸ (5-pin) / 3-wire	Binder series 723 ⁸ (7-pin) / 2-wire with communication interface	cable colours (IEC 60757)
Supply +	3	3	3 / wh (white)	wh (white)
Supply -	1	4	1 / bn (brown)	bn (brown)
Signal + (for 3-wire)	-	1	(6) / gn (green)	gn (green)
RxD	-	-	4 / ye (yellow)	-
TxD	-	-	5 / gr (gray)	-
GND	-	-	7 / gn (green)	-
Shield	5	5	2 / gnye (green-yellow)	gnye (green-yellow)

⁸ in separated version


Dimensions (in mm)

standard






separated version

option




version with
corrugated pipe

Mounting flange with cable gland		
Technical data		
Suitable for	all probes	
Flange material	stainless steel 1.4404 (316L)	
Material of cable gland	standard: brass, nickel plated on request: stainless steel 1.4305 (303); plastic	
Seal insert	material: TPE (ingress protection IP 68)	
Hole pattern	according to DIN 2507	
Version	Size (in mm)	Weight
DN25 / PN40	D = 115, k = 85, b = 18, n = 4, d = 14	1.4 kg
DN50 / PN40	D = 165, k = 125, b = 20, n = 4, d = 18	3.2 kg
DN80 / PN16	D = 200, k = 160, b = 20, n = 8, d = 18	4.8 kg
Ordering type		Ordering code
DN25 / PN40 with cable gland brass, nickel plated		ZMF2540
DN50 / PN40 with cable gland brass, nickel plated		ZMF5040
DN80 / PN16 with cable gland brass, nickel plated		ZMF8016
Terminal clamp		
Technical data		
Suitable for	all probes with cable \varnothing 5.5 ... 10.5 mm	
Material	standard: steel, zinc plated optionally: stainless steel 1.4301 (304)	
Weight	approx. 160 g	
Ordering type		Ordering code
Terminal clamp, steel, zinc plated		Z100528
Terminal clamp, stainless steel 1.4301 (304)		Z100527
Display program		
<p>CIT 200 Process display with LED display</p> <p>CIT 250 Process display with LED display and contacts</p> <p>CIT 300 Process display with LED display, contacts and analogue output</p> <p>CIT 350 Process display with LED display, bargraph, contacts and analogue output</p> <p>CIT 400 Process display with LED display, contacts, analogue output and Ex-approval</p> <p>CIT 600 Multichannel process display with graphics-capable LC display</p> <p>CIT 650 Multichannel process display with graphics-capable LC display and datalogger</p> <p>CIT 700 Multichannel process display with graphics-capable TFT monitor, touchscreen and contacts</p> <p>PA 440 Field display with 4-digit LC display</p> <p>For further information please contact our sales department or visit our homepage: http://www.bdsensors.com</p>		
		 <p>cable gland M16x1.5 with seal insert (for cable-\varnothing 4 ... 11 mm)</p>
		
		

© 2016 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code LMP 308i

LMP 308i



Pressure																	
	in bar	4	4	0													
	in mH ₂ O	4	4	1													
Input																	
	[mH ₂ O]	4	0	0	0												
	[bar]	10	1	0	0	1											
		20	2	0	0	1											
		40	4	0	0	1											
		100	1	0	0	2											
		200	2	0	0	2											
	customer		9	9	9	9											consult
Housing																	
	Stainless steel 1.4404 (316L)					1											
	customer					9											consult
Diaphragm																	
	Stainless steel 1.4435 (316L)					1											
	customer					9											consult
Output																	
	4 ... 20 mA / 2-wire								1								
	Intrinsic safety 4 ... 20 mA / 2-wire								E								
	0 ... 10 V / 3-wire								3								
	customer								9								consult
Seals																	
	FKM								1								
	EPDM								3								
	customer								9								consult
Electrical connection																	
	PVC-cable ¹									1							
	PUR-cable ¹									2							
	FEP-cable ¹									3							
	customer									9							consult
Accuracy																	
	0.1 % ²									1							
	customer									9							consult
Cable length																	
	in m										9	9	9				consult
Version																	
	standard											1	1	1			
	with communication interface ³											1	2	1			
	prepared for mounting ⁴																
	with stainless steel pipe																consult
	cable protection with																
	stainless steel corrugated pipe																
	with pipe length in m																consult
	customer																consult

¹ cable with integrated air tube for atmospheric pressure reference

² available on request: calibration of individual pressure range higher than 400 mbar with accuracy 0.1 %

³ Software, interface and cable have to be order separately (Ordering code: CIS-G; Software appropriate for Windows[®] 95, 98, 2000, NT Version 4.0 or newer and XP)

⁴ stainless steel pipe is not part of the supply

Windows[®] is a registered trademark of Microsoft Corporation

This document contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

