ADDITIONAL SPECIFICATIONS FOR CALIBRATION OF TRANSMITTERS WITH PROCESS CONNECTIONS

Dear customer,

please complete this form and send it back within 3 working days after order by fax using the following number +49 (0) 9235 / 98 11-11. If no additional specification will be made, the transmitter will be calibrated according BD SENSORS standards.

Company: .....

Order number: ..... Order position: .....

Please fill here Type and ordering number of transmitter:

Calibration temperatures

Standard (without specification)

Ambient temperature 20 °C

Option (please mark)

○ Calibrate by medium temperature ..... °C (38.- € net. additional)

valid for following conditions:

- ► surrounding: ambient temperature 20 °C
- ► max. calibration temperatures: 200 °C
- ► compensation range: ± 25 °C
- ► for vacuum ranges < 250 mbar: max. calibration temperature is 70 °C.
- ► with vacuum ranges or nominal pressure abs. and calibration temperature higher 70 °C please contact sales department

Installation position (for pressure ranges up to 4 bar; with higher pressure ranges the installation position is negligible)

Standard (without specification)

0°



Option (please mark)

○ 180°



○ 90°



○ other

Other information

Working temperature range: from ..... up to ..... °C

Medium in normal operation: .....

Temperature at the cleaning / sterilisation: max. ..... °C

Medium for the cleaning / sterilisation: .....

..... BD SENSORS job number

Date and signature: .....

BD SENSORS GmbH
BD-Sensors-Straße 1
D - 95199 Thierstein

Telefon +49 (0) 92 35 / 98 11- 0
Telefax +49 (0) 92 35 / 98 11- 11

www.bdsensors.com
info@bdsensors.com